


1 MAIN FLOOR PLAN
 1/4"=1'-0"
 0 4'

- GENERAL NOTES**
- CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITIONS AND NOTIFY ARCHITECT OF ANY DISCREPANCIES
 - SIGNS THAT DISPLAY THE INTERNATIONAL SYMBOL OF ACCESSIBILITY SHALL BE INSTALLED ON THE WALL, ON THE LATCH SIDE OF THE RESTROOM DOOR. THESE SIGNS SHALL BE MOUNTED 60 INCHES TO THE CENTER OF THE SIGNS FROM THE FLOOR, PER ADA 4.30.6
 - COFFEE EQUIPMENT SUPPLIED BY OWNER INSTALLED BY G.C.

DOOR TYPES AND HARDWARE		PARTITION TYPES	
MARK	DESCRIPTION		
1	RESTROOM (1 1/2 PR) BUTT HINGES (1) FLOOR STOP (4) SILENCERS (1) LEVER LOCKSET (PRIVACY) (1) CLOSER		
2	EXT. ALUM. ENTRY DOOR (SHELL SCOPE) (1) CONTINUOUS HINGE (1) THRESHOLD (1) PANIC EXIT DEVICE (1) CLOSER (1) WEATHER STRIPPING (1) PULL		
3	EXT. EXIT DOOR (SHELL SCOPE) (1) THRESHOLD (1) PANIC EXIT DEVICE (1) CLOSER (1) PULL (1) WEATHER STRIPPING *FOR TENANT PKG. ADD SECURITY PEEPHOLE		

- NOTES:**
- FULL SOUND BATT INSULATION IN TENANT DEMISING WALLS, CHASE WALLS, AND RESTROOM WALLS.
 - SOUND SEALANT AT CORNER JOINTS OF CONCRETE FLOOR AND WALLS WITH SOUND BATT INSULATION.
 - WATER-RESISTANT GYP BD AT ALL RESTROOMS AND WET AREAS.
 - TILE BACKER BOARD AT ALL TILE LOCATIONS.



CITY PERMIT SET
 26 JUN 2015
 NHP PERMIT SET
 09 APR 2015

FLOOR PLAN
 PARTITION SCHED.
 GEN. NOTES